

# SOLID 50A3-3

## Ideal for:

- Just-in-time applications
- On-demand printing
- Business and workflow documents
- ecommerce

## HIGHLIGHTS / FEATURES / SPECIAL ATTRIBUTES

- Breakneck 3 seconds to printing of first page
- Duplex printing at full speed (up to 26 pages/minute)
- Flexible extension options for paper feed and tray
- Full integration in production lines through SPS control

## TOP PERFORMANCE FOR OFFICES AND LOGISTICS



### SOLID 50A3-3

When just-in-time applications and top printing performance really matters, the SOLID 50A3-3 professional laser printer is the perfect choice: the first page is printed in less than 3 seconds and this model boasts printing speeds of up to 50 pages per minute. It combines the highest level of reliability with versatile paper handling capabilities. Optional face-up output and the SPS control option provide with the unique Microplex controller supplying the intelligence for the best prerequisites for integrating the SOLID 50A3-3 in production lines where control and "hand shake" is the absolute requirement.

## Print Engine

<b>Print technology</b>	Laser, OPC heat / pressure
<b>Controller</b>	MPC 5.2 with Intel XScale PXA 255 (400-MHz-RISC-Processor)
<b>Print speed</b>	up to 50 pages/minute (A4) first page: < 3s
<b>Print resolution</b>	max. 600 dpi x 600 dpi
<b>Duty cycle</b>	up to 50.000 pages (A4) (based on a using period of 60 months) max. 250.000 pages (A4)
<b>Power supply</b>	220-240 V /50/60 Hz
<b>Power consumption</b>	8A
<b>Dimensions (WxDxH in mm)</b>	640 x 559 x 483
<b>Weight</b>	48kg (incl. consumables)
<b>Environment temperature</b>	10 - 32°C
<b>Relative humidity</b>	20 - 80 % (rel., non condensing)
<b>Interfaces</b>	Serial: USB, RS232, RS422 Parallel: IEEE 1284 (Centronics) LAN: Ethernet-Interface 10/100 MBit, bi-directional (TCP/IP)
<b>Memory</b>	RAM: 128MB Flash: 16MB

## MPC 5.2 High-End Print-Controller

### Emulations

MICROPLEX IDOL, HP-PCL5/ HPGL, AGFA Reno,  $\mu$ -Postscript, LN03+, BULL-MP6090, Etimark MP-1220, TEC Bx72, TEC B6xx, Diablo 630, IBM Proprinter, EPSON FX-80, MT-600/MT40, IDS, ANSI Genicom, TIFF, XML (SAP RFID), CUPS Raster

### Optional Emulations

CODE-V (Magnum), XEROX XES, KODESCRIPT+, Prescribe/PSB 2, IGP-10, Datamax (FGL), Datamax Labelpoint, LDC, ZPL II, EPL 2, UPI Fingerprint, IER Command, Godex EZPL, HP Designjet, IPDS, AEA, AFP, Status-Out (more emulations on request)

### Barcodes

Codebar, Code39, MSI, PDF417, Interleaved 2/5, Interleaved 2/5 (3-Strich Datalogic), Interleaved 2/5 (3-Strich Matrix), EAN-8, 13, 128, Add-On-Codes, Code11, Code93, Code 128, UPC-A, UPC-E

### Optional Barcodes

Datamatrix, Maxi-Code, QR Code, Aztec-Code, USD-5 (more barcodes on request)

### Additional functions

<b>Intelligent barcode generation</b>	on-the-fly in the printer
<b>Format splitting</b>	in several subformats by command
<b>Integrated form management</b>	up to 12 MB flash for forms and fonts inside the printer

### Optional functions

#### Status-out

gives notice of each correctly printed page via interface


#### SPS-Control (EMBEDDED INTELLIGENCE - Enabling two-way communication between printer and a PLC)

integration of the printer into production lines is possible, controlled by SPS-interface.



## Printable Media

<b>Size</b>	A5 bis A3
<b>Weight</b>	64-163 g/m <sup>2</sup> Duplex 60-120 g/m <sup>2</sup>



## Paper Path

### Input

cassette 1, 500 sheets (A5 to A3)  
cassette 2, 500 sheets (A5R\* to A3)  
manual input, 100 sheets (A5 to A3)

### Optional

cassette 3+4, 500 sheets (A5R\* to A3)  
2.000 sheets feeder (A4, Letter)

### Output

500 sheets, face down  
duplex unit

### Optional

100 sheets, face up  
3.500 sheets finisher/stacker with stapler+puncher,  
(50 sheets per batch)

\*A5R = A5 short side feeding

The brand names referred to are the registered trademarks of the respective companies. All figures and details in italics and highlighted in color are optional. Technical data is subject to change. The information contained in this specification sheet refers exclusively to the described details and not to warranted characteristics. No guarantee is assumed. The information do not exempt from the obligation for inspection of each respective individual case. Version 16.06.2017



Microplex Printware AG  
Panzerstraße 5 | 26316 Varel | Germany  
phone +49 4451 91 37-0 | fax +49 4451 91 37-49



PRINTING TECHNOLOGIES  
ENGINEERED IN GERMANY

www.microplex.de